

Explorer 4

Rack multichannel control unit for marine applications

- 4 channels in 4-20 mA
- Backlit display
- Rack mounting facility
- Modular till 4 units for 16 sensors







Explorer 4 is the multichannel control unit gathering just one rack till 4 acquisition channels.

The system has been planned for the monitoring in continuous of gas and other different parameters, through the related alarms check. All is included in a rack of easy installing container.

The rack can be 8 or 16 channels made, useful to monitoring more point.

Each independent channel is supplied with 3 relays in outlet. The setup is done through the 3 buttons placed on the front side.

The unit gives the power supply to the sensors transmitters in 4-20 mA and a serial unit RS232 for the configuration can be added.

Purchase Order details	Explorer 4	Cod. 1004050	
	=xpiorer i	200. 200 1000	

S		
Rack, modular with 4 - 8 – 16 channels		
4 channels Rack:		
depth 105mm (21U) x height 132,5mm (3HE)		
1,7kg.		
LCD 2x16 digit		
18 – 28 VDC/110 – 220 VAC		
5 – 25 W		
4-20mA 2 or 3 conductors		
RS 232 with BUS for I/O to the PC		
4-20mA, 2 or 3 conductors		
 4 LED for channels (1 fault and 3 alarm levels) 		
 1 LED for power supply 		
Active Buzzer if alarm occurs		
Nr. 1 relay: general alarm		
 Nr. 1 relay for fault signal, typical of the 4 channels 		
-20°C to + 55°C		
0% to 95% low levels of humidity (not condensing)		
Language (Italian, English)		
 Gain, offset, and range for each channel 		
 Alarm levels 		
 Channel sample time 		
CE – Electromagnetic Compatibility		
RINA ELE 272113CS		
MED 272113CS		
ABS 13-GE975317-PDA		